

UNITED STATES PATENT AND TRADEMARK OFFICE



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/718,961	11/21/2003	Clifford C. Bampton	024.0037	4430	
29906				EXAMINER	
7150 E. CAME	FISHER & LORENZ, P.C. ELBACK, STE. 325		MCGUTHRY BANKS, TIMA MICHELE		
SCOTTSDALI	E, AZ 85251		ART UNIT	PAPER NUMBER	
			1793		
			MAIL DATE	DELIVERY MODE	
			01/09/2008	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		Application No.	Applicant(s)	
		10/718,961	BAMPTON, CLIFFORD C.	
•	Office Action Summary	Examiner	Art Unit	
		Tima M. McGuthry-Banks	1793	
	The MAILING DATE of this communication app	ears on the cover sheet with the c	orrespondence address	
WHIC - Exter after - If NO - Failu Any	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DATE of time may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. It period for reply is specified above, the maximum statutory period were to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing and patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be timulated will expire SIX (6) MONTHS from a cause the application to become ABANDONEI	L. lely filed the mailing date of this communication. D (35 U.S.C. § 133).	
Status				
2a) <u></u> □	Responsive to communication(s) filed on 29 Or This action is FINAL . 2b) This Since this application is in condition for allower closed in accordance with the practice under Expression 1.	action is non-final. nce except for formal matters, pro		
Dispositi	on of Claims			
5)□ 6)⊠ 7)□	Claim(s) 1-7,9-15,17-20 and 24 is/are pending 4a) Of the above claim(s) is/are withdray Claim(s) is/are allowed. Claim(s) 1-7, 9-15, 17-20, 24 is/are rejected. Claim(s) is/are objected to. Claim(s) are subject to restriction and/or	vn from consideration.		
Applicati	on Papers			
10)	The specification is objected to by the Examine The drawing(s) filed on is/are: a) accomplicant may not request that any objection to the Replacement drawing sheet(s) including the correct The oath or declaration is objected to by the Examine	epted or b) objected to by the Eddrawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).	
Priority u	ınder 35 U.S.C. § 119			
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 				
2) Notice 3) Information	t(s) te of References Cited (PTO-892) te of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO/SB/08) or No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ite	

Art Unit: 1793

DETAILED ACTION

Status of Claims

Claims 1, 6, 9, 14 and 20 are currently amended, Claims 2-5, 10-13, 15, 17-19, and 24 are original, and Claims 8, 16 and 21-23 are canceled.

Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claim 1 is rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. The limitation of "consolidating" in the preamble is not in the specification as originally filed.

Claims 9 and 20 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. The limitation of "to form additional <u>stacked</u> solid layers" is the step of "building up" is not in the specification as originally filed.

Art Unit: 1793

Claim 18 is rejected under 35 U.S.C. 112, first paragraph, as based on a disclosure which is not enabling. The step of "performing said metal liquid phase sintering and isothermal solidification process" is critical or essential to the practice of the invention, but not included in the claim(s) is not enabled by the disclosure. See *In re Mayhew*, 527 F.2d 1229, 188 USPQ 356 (CCPA 1976). It is unclear where the "performing" step occurs in the process, since there is nothing in the claim that establishes support for a liquid phase sintering and isothermal solidification process.

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Claim 18 recites the limitation "said metal liquid phase sintering and isothermal solidification process" in lines 1 and 2. There is insufficient antecedent basis for this limitation in the claim.

Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

Claims 1 and 2 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al (US 6,719,948 B2) in view of Feldstein (US 5,248,475).

Lorenz et al teaches forming a skeleton or green part from powder metallurgy. Further processing includes using an infiltrant with a melting point depressant (MPD). The MPD diffuses into the skeleton, the liquid undergoes a diffusional solidification and the material eventually solidifies. Regarding melting the alloying metal, the infiltrant has a composition

Art Unit: 1793

similar to that of the skeleton (column 2, lines 32-48 and column 3, lines 16-23). The powder metallurgy process to make the skeleton produces a homogeneous net shape (column 3, lines 4-6). Titanium alloys can be used in this process (column 23, lines 45-50). The infiltrant is molten (column 3, line 29); the composition of the melt is established by, *inter alia*, separating the infiltrant from the melt prior to infiltration and adding excess skeleton material to the melt (lines 36-38). Regarding Claim 2, the alloying element with Ti includes Sn (column 23, line 52). However, Lorenz et al does not disclose the steps of spreading, directing and re-solidifying as in Claim 1.

Feldstein teaches a method for fabricating a sintered and solid element. The steps include, *inter alia*, coating discrete pieces of an "unsinterable" material with an alloying agent, exposing the discrete pieces to heat so that localized melting occurs to form molten surfaces on the discrete particles, and removing the heat away from the element (column 5, lines 1-46). The heat source is not specificed in Feldstein, but the disclosed controlled heating reads on an energy beam. Titanium-based alloys can be used with alloying agents such as Sn and Ni (lines 55-58). It would have been obvious to one of ordinary skill in the art at the time the invention was made to use the fabricating technique in Feldstein for the skeleton in Lorenz et al, since Feldstein teaches that the alloyed element concentration profile can be controlled, distribution is optimized, and costs of production are minimized (column 4, lines 11-18).

Claim 3 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claims 1 and 2 above, and further in view of Rongti et al (2000).

Lorenz et al in view of Feldstein discloses the invention substantially as claimed.

However, Lorenz et al view of Feldstein does not disclose the concentration of tin as claimed.

Art Unit: 1793

Rongti et al discloses that Sn addition to Ti can improve the wetting behavior of Ti on substrates and discloses a composition of 10% Sn (pages 21 and 24). It would have been obvious to one of ordinary skill in the art at the time the invention was made to use a 10% Sn composition as taught by Rongti et al in the alloy of Lorenz et al in view of Feldstein to improve wetting.

Claims 4 and 5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claims 1 and 2 above, and further in view of the CRC Handbook of Chemistry and Physics.

Lorenz et al in view of Feldstein discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein does not disclose the operating temperatures as claimed. The CRC Handbook discloses the melting temperature of Ti (≈ 3020 °F) and Sn (≈ 448 °F). It would have been obvious to one of ordinary skill in the art at the time the invention was made that the operating temperature would be between the melting temperatures of Ti and Sn, since the alloying element melts and the main element, i.e. Ti, remains in the solid state.

Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claim 1 above, and further in view of Clement et al (US 6,223,976).

Lorenz et al in view of Feldstein discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein does not disclose the alloy concentration as claimed. Clement et al discloses a process for repairing and refacing titanium aluminide articles by preparing a mixture of powders consisting of 40-90% powder A and 10-2=40% powder B (abstract). Powder A is the same composition as the article to be refaced or repaired, whereas powder B is Cu15 Ni15, balance Ti (column 4, lines 13-59). An obvious advantage of the

Art Unit: 1793

addition of the Ti-15Cu-15Ni alloy is the lower melting temperature relative to the alloys disclosed in Clement et al. This feature would enable repair and refacing to be made at a temperature less than that of the article to be repaired. It would have been obvious to one of ordinary skill in the art at the time the invention was made to add between 10 and 40% of Ti-15Cu-15Ni as taught by Clement et al to the alloy composition of Lorenz et al in view of Feldstein to enable deposition to be made at lower temperatures.

Claim 7 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein and Clement et al as applied to claims 1 and 6 above, and further in view of the CRC Handbook.

Lorenz et al in view of Feldstein and Clement et al discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein and Clement et al does not disclose the operating temperature as claimed. The CRC Handbook discloses the melting temperature of Ti (≈ 3020 °F) and Sn (≈ 448 °F). It would have been obvious to one of ordinary skill in the art at the time the invention was made that the operating temperature would be between the melting temperatures of Ti and Sn, since the alloying element melts and the main element, i.e. Ti, remains in the solid state.

Claims 9, 10 and 17 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein.

Lorenz et al teaches forming a skeleton or green part from powder metallurgy. Further processing includes using an infiltrant with a melting point depressant (MPD). The MPD diffuses into the skeleton, the liquid undergoes a diffusional solidification and the material eventually solidifies. Regarding melting the alloying metal, the infiltrant has a composition

Art Unit: 1793

similar to that of the skeleton (column 2, lines 32-48 and column 3, lines 16-23). The powder metallurgy process to make the skeleton produces a homogeneous net shape (column 3, lines 4-6). Titanium alloys can be used in this process (column 23, lines 45-50). The infiltrant is molten (column 3, line 29); the composition of the melt is established by, *inter alia*, separating the infiltrant from the melt prior to infiltration and adding excess skeleton material to the melt (lines 36-38). Regarding the step of spreading, Feldstein teaches making sintered layers (column 6, liens 18-27). Regarding Claim 10, the alloying element with Ti includes Sn (column 23, line 52). However, Lorenz et al does not disclose the steps of spreading, directing and re-solidifying as in Claim 9 or the size of the powder blend as in Claim 17.

Feldstein teaches a method for fabricating a sintered and solid element. The steps include, *inter alia*, coating discrete pieces of an "unsinterable" material with an alloying agent, exposing the discrete pieces to heat so that localized melting occurs to form molten surfaces on the discrete particles, and removing the heat away from the element (column 5, lines 1-46). The heat source is not specificed in Feldstein, but the disclosed controlled heating reads on an energy beam. Titanium-based alloys can be used with alloying agents such as Sn and Ni (lines 55-58). Regarding Claim 9, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the fabricating technique in Feldstein for the skeleton in Lorenz et al, since Feldstein teaches that the alloyed element concentration profile can be controlled, distribution is optimized, and costs of production are minimized (column 4, lines 11-18). Regarding Claim 17, the discrete pieces in Feldstein can be from particles to chopped pieces of fiber, wire, platelets or discs (column 4, lines 32-36). In the case where the claimed ranges

Art Unit: 1793

overlap or lie inside ranges disclosed by the prior art, a *prima facie* case of obviousness exists. See MPEP § 2144.05.

Claim 11 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claims 9 and 10 above, and further in view of Rongti et al.

Lorenz et al in view of Feldstein discloses the invention substantially as claimed. However, Lorenz et al view of Feldstein does not disclose the concentration of tin as claimed. Rongti et al discloses that Sn addition to Ti can improve the wetting behavior of Ti on substrates and discloses a composition of 10% Sn (pages 21 and 24). It would have been obvious to one of ordinary skill in the art at the time the invention was made to use a 10% Sn composition as taught by Rongti et al in the alloy of Lorenz et al in view of Feldstein to improve wetting.

Claims 12 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claims 9-11 above, and further in view of the CRC Handbook.

Lorenz et al in view of Feldstein discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein does not disclose the operating temperatures as claimed. The CRC Handbook discloses the melting temperature of Ti (\approx 3020 °F) and Sn (\approx 448 °F). It would have been obvious to one of ordinary skill in the art at the time the invention was made that the operating temperature would be between the melting temperatures of Ti and Sn, since the alloying element melts and the main element, i.e. Ti, remains in the solid state.

Claim 14 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein as applied to claim 9 above, and further in view of Clement et al.

Art Unit: 1793

Lorenz et al in view of Feldstein discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein does not disclose the alloy concentration as claimed. Clement et al discloses a process for repairing and refacing titanium aluminide articles by preparing a mixture of powders consisting of 40-90% powder A and 10-2=40% powder B (abstract). Powder A is the same composition as the article to be refaced or repaired, whereas powder B is Cu15 Ni15, balance Ti (column 4, lines 13-59). An obvious advantage of the addition of the Ti-15Cu-15Ni alloy is the lower melting temperature relative to the alloys disclosed in Clement et al. This feature would enable repair and refacing to be made at a temperature less than that of the article to be repaired. It would have been obvious to one of ordinary skill in the art at the time the invention was made to add between 10 and 40% of Ti-15Cu-15Ni as taught by Clement et al to the alloy composition of Lorenz et al in view of Feldstein to enable deposition to be made at lower temperatures.

Claim 15 is rejected under 35 U.S.C. 103(a) as being unpatentable over Lorenz et al in view of Feldstein and Clement et al as applied to claims 9 and 14 above, and further in view of the CRC Handbook.

Lorenz et al in view of Feldstein and Clement et al discloses the invention substantially as claimed. However, Lorenz et al in view of Feldstein and Clement et al does not disclose the operating temperature as claimed. The CRC Handbook discloses the melting temperature of Ti (≈ 3020 °F) and Sn (≈ 448 °F). It would have been obvious to one of ordinary skill in the art at the time the invention was made that the operating temperature would be between the melting temperatures of Ti and Sn, since the alloying element melts and the main element, i.e. Ti, remains in the solid state.

Art Unit: 1793

Claims 20 and 24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Feldstein in view of Clement et al.

Feldstein teaches fabricating a sintered and solid element. The steps include, *inter alia*, coating discrete pieces of an "unsinterable" material with an alloying agent, exposing the discrete pieces to heat so that localized melting occurs to form molten surfaces on the discrete particles, and removing the heat away from the element (column 5, lines 1-46). Titanium-based alloys can be used with alloying agents such as Sn and Ni (lines 55-58). Feldstein also teaches making sintered layers (column 6, lines 18-27). Regarding Claim 24, Feldstein does not disclose using a binder, which reads on not including a carbon-based polymer. However, Feldstein does not disclose the alloy concentration as claimed.

Clement et al discloses a process for repairing and refacing titanium aluminide articles by preparing a mixture of powders consisting of 40-90% powder A and 10-2=40% powder B (abstract). Powder A is the same composition as the article to be refaced or repaired, whereas powder B is Cu15 Ni15, balance Ti (column 4, lines 13-59). An obvious advantage of the addition of the Ti-15Cu-15Ni alloy is the lower melting temperature relative to the alloys disclosed in Clement et al. This feature would enable repair and refacing to be made at a temperature less than that of the article to be repaired. It would have been obvious to one of ordinary skill in the art at the time the invention was made to add between 10 and 40% of Ti-15Cu-15Ni as taught by Clement et al to the alloy composition of Feldstein to enable deposition to be made at lower temperatures.

Art Unit: 1793

Response to Arguments

Applicant's arguments with respect to claims 1-7, 9-15, 17-20 and 24 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Huang et al (US 6,042,780) discloses a method for hot isostatic pressing materials produced by selective laser sintering or coatings (column 1, lines 49-53 and column 8 lines 11-16). The pressing occurs at a temperature not exceeding 1800 °C (column 13, lines 23-26) at pressures as high as 1 GPa (column 12, lines 25-31). Huang et al also discloses processing Ti-6Al-4V powder in an inert atmosphere (column 11, lines 52-59).

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tima M. McGuthry-Banks whose telephone number is (571) 272-2744. The examiner can normally be reached on M-F 7:00 am - 3:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Roy King can be reached on (571) 272-1244. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 1793

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 1700